



Geo N.
Mitchell Drilling Company, Inc.

P.O. Box 550
1239 County Road 1500 N
Carmi, IL 62821
618-382-2343
618-384-2435 Fax
1-877-382-5032
www.mitchell-drilling.com
email: nrgy@mitchell-drilling.com

RIG #1

DEPTH RANGE:	5,000 feet
DRAWWORKS:	MAC "300". Powered by 12.5 L-60 Series Detroit Engine 475HP
DERRICK:	P.J. 96' Double with 300,000# Hook Load
BASE:	18" H x 14' W x 40' L
PRIMARY PUMP:	Continental EMSCO D375, 7 1/2" x 14" with 6" liners. Powered by 14L-60 Series Detroit Engine 475HP
STANDBY PUMP:	See list of optional equipment.
BLOWOUT PREVENTERS & ACCUMULATORS:	See list of optional equipment.
ROTARY TABLE:	Oilwell 17 1/2"
BLOCK & HOOK:	McKissick, 3 Sheave, 150 Ton - Combination Block & Hook
SWIVEL:	Gardner-Denver 125
KELLY:	4 1/4" x 40'-square
DRILL PIPE:	4500' x 4 1/2" X-Hole, Grade E 16.60#
DRILL COLLARS:	(16) – 6 1/2" x 31' X-Hole
ASSOCIATED EQUIPMENT:	Sure Shot Model "A" Straight Hole Tool, Pilot II Automatic Driller, Martin & Decker "Clipper" Weight Indicator, Halliburton Wireline & Measuring Device, John Deere 20 KW Light Plant, 2000 Gallon Fuel Tank, 110 Barrel Water Storage Tank, Slips & Elevators, One Lombardini Diesel Water Pump, One Homelite Gasoline Water Pump, One Centrifugal Washdown Pump, Pipe Racks & Tubs.
COMMUNICATION:	24-hour communication between rig, toolpusher, drilling superintendent and/or Carmi, Illinois office via radio and/or mobile phone.